

21 and 22 Series Filter Housings



STANDARD HOUSING DESIGN

- Body: Carbon steel
- Interior and exterior: Epoxy coated
- Head: Anodized die cast aluminum
- Design pressure: 150 psi
- Closure: Thru-bolts
- Closure seal: Buna-N o-ring—other materials available upon request
- Vent and drain connections with brass petcocks provided
- Inlet and outlet connections: 1½" NPT female threaded
- One filter cartridge installed

OPTIONS

- Pop up Δ P indicator - 15, 25 psi
- Piston Type indicator - 15 psi

The Facet 21 and 22 Series filter housings are economical, compact housings for superior in-line filtration protection when used with Facet's standard 21 or 22 Series filter cartridges to remove solids from aviation fuels.

Both the exteriors and interiors of the Facet 21 and 22 Series filter housings carbon steel bodies are epoxy coated to protect against corrosion. These sturdy, single cartridge housings are easy to maintain and require only 2" (51 mm) base clearance for cartridge change out.



pop up indicator



piston type indicator

HOUSING DATA

MODEL NUMBER ⁽¹⁾	OPERATING PRESSURE		INLET / OUTLET CONNECTIONS NPT	NOMINAL LENGTH		SHIPPING WEIGHT		OUTSIDE DIAMETER	
	psi	kPa		in.	mm.	lbs.	kgs.	in.	mm.
21 SERIES									
VF-21-609-2PLO	150	1034	1½"	16	406	13	5.9	6½"	165
22 SERIES									
VF-22-612-2PLO	150	1034	1½"	20	508	17	7.5	6½"	165

(1) Model number includes housing and required cartridge installed

MODEL LEGEND

HOUSING	SERIES	ELEMENT TYPE	OPTIONS
VF	21	CF-609-2PLO CF-609-5PLO	PU15 = 15 psi pop up indicator PU25 = 25 psi pop up indicator PG = piston type
VF	22	CF-612-2PLO CF-612-5PLO	

Due to our continuing program of improvement, specifications are subject to change without notice.