

---

**SUPPLYING CLEAN AIR TO INDUSTRY**

**MODEL AQE4000**  
**Overhead Cartridge System**



*The new Overhead Cartridge System is a self-contained, continuous-cleaning cartridge media air cleaner for use in source capture applications in industry. The Model AQE4000 can be ordered in one and two arm configurations or permanently ducted to capture contaminants such as welding smoke, grinding dust, plastic and other fine particles.*

**Precision Filtration Products**

YOUR ONE  FOR FILTERS

---

---

# AQE4000 FEATURES & SPECIFICATIONS

## Principles of Operation:

Airborne contaminants enter the AQE4000 through the optional hood/arm assembly at a rate of 1250 cubic feet of air per minute (cfm) per arm. Heavy particles are propelled downward through the venturi and into the clean out drawer. Small submicron particles are then trapped within the pleats of the four 99.8% efficient cartridge filters. The cleaned air is then discharged through the back of the unit. The cartridge filters are cleaned automatically using a Goyen valve reverse pulse system and solid state automatic control timer.

## STANDARD FEATURES:

- Automatic cleaning system
- Solid State, Control Timer
- 5 hp TEFC motor
- 1100 square feet of media
- 99.8% efficient at .5 micron
- Disconnect and overload protection
- Three year limited warranty

## OPTIONAL FEATURES:

- Externally supported 11' and 14' arms with 360° rotation
- Double arm configuration
- Photohelic controller
- Hood mounted blower controls
- Hood mounted halogen light

## CONTROLS:

All models include control circuitry and thermal protection.

## SPECIFICATIONS:

DIMENSIONS:	21" H x 58" W x 98" D
WEIGHT:	Unit 656 lbs. Optional Arm: 11' -68 lbs., 14' - 73 lbs.
ARM ASSEMBLY (OPTIONAL):	14' and 11' long x 8" diameter. Externally supported arm with full 360° arm rotation. Arm assembly incorporated a gas spring which provides easy up and down movement. 18 ga. aluminum hood with handle. Hood moves easily vertically and horizontally.
AIR FLOW VOLUME:	2500 cfm total. 1250 per arm.
MOTOR:	5 HP TEFC
BLOWER:	Direct drive, backward incline. Air Foil Wheel 13.5" diameter.
CABINET CONSTRUCTION:	16 Ga. welded steel
CONTROL TIMER:	Pulse frequency adjustable from 15 seconds to 20 minutes.
POWER:	208-240V 13.4 amps max 3 phase 440-480V 6.6 amps max 3 phase
FINISH:	Durable baked enamel paint
FILTRATION:	Four high efficiency cartridge filters. 12 3/4" diameter x 30" 1100 sq. ft. total. 99.8% efficient at .5 micron
FILTER ACCESS:	End load through access covers.
FILTER CLEANING:	Self-Cleaning Reverse Pulse Jet System which utilizes two, one inch Goyen diaphragm valves. Requires 80-120 psi of shop supplied compressed air.
NOISE LEVEL:	79 dBa at 6'
WARRANTY:	Limited three year warranty

