

## ST-5 and SS-5 Series Separator Cartridges Qualified to API 1581, 5th Edition



**TEFLON SERIES** 

Facet's **ST-5 Series** Teflon separator cartridges are cleanable and reusable separator cartridges of the highest quality in a variety of dimensional configurations. Teflon® coated screen is wrapped around a treated, perforated metal shell, lock-seam folded and secured by metal clips, then adhesive bonded to gasketed metal end caps. The screen is Teflon® coated for more effective water repelling characteristics assuring long, trouble-free service.

Facet's **SS-5 Series** synthetic separator cartridges feature a specially developed hydrophobic synthetic media which offers all the permanent features of Teflon® screen, with the ability to handle higher flow rates. Synthetic mesh is wrapped around a treated, perforated metal shell, then adhesive-bonded to gasketed metal end caps. The synthetic mesh is designed for more effective water repelling characteristics, assuring long, trouble-free service.

Both Facet ST-5 and SS-5 Series Separators have the distinctive Facet Velocigard which provides balanced flow of product (radially inward) throughout the cartridge. All metal components are treated to resist corrosion. Maximum recommended operating temperature is 240°F. For compatability in extreme operating conditions, other gasket, adhesive and metal materials are available.

#### STANDARD DESIGN FEATURES

- Cleanable and reusable
- Superior water barrier
- Recommended maximum operating temperature: 240°F
- pH range from 5 to 9
- Designed for balanced flow through cartridge
- Flow direction: Outside to inside

#### **MATERIALS**

- Synthetic mesh OR Teflon® coated screen
- Treated metal components for corrosion protection
- Buna-N gaskets
- Other gasket, adhesive and metal materials are available on request



**SYNTHETIC SERIES** 

Due to our continuing program of improvement, specifications are subject to change without notice.



# ST-5 and SS-5 Series Separator Cartridges Qualified to API 1581, 5th Edition

### **DIMENSIONAL INFORMATION**

MODEL NUMBER	MODEL NUMBER	OUTSIDE I	DIAMETER	NOMINAL LENGTH		INSIDE DIAMETER SEALING END		INSIDE DIAMETER MOUNTING END	
TEFLON	SYNTHETIC	in.	mm.	in.	mm.	in.	mm.	in.	mm.
ST318FA-5	SS318FA-5	3	76	18	460	BLIND	13	2	51
ST324FA-5	SS324FA-5	3	76	24	610	BLIND	13	2	51
ST412FC-5	SS412FC-5	41/8	105	11½	290	<b>1</b> 7// <sub>8</sub>	48	17/8	48
ST415FB-5	SS415FB-5	41/2	114	15	380	BLIND	13	31/2	89
ST417FB-5	SS417FB-5	41/2	114	17	430	BLIND	13	31/2	89
ST422FC-5	SS422FC-5	41/8	105	221/2	570	17/8	48	17/8	48
ST424FB-5	SS424FB-5	41/2	114	24	610	BLIND	13	31/2	89
ST430FB-5	SS430FB-5	41/2	114	30	760	BLIND	13	31/2	89
ST432FC-5	SS432FC-5	41/8	105	31½	800	17/8	48	17/8	48
ST436FB-5	SS436FB-5	41/2	114	36	910	BLIND	13	31/2	89
ST609FB-5	SS609FB-5	6	152	9	230	BLIND	13	31/2	89
ST609FF-5	SS609FF-5	6	152	9	230	BLIND	13	41/2	114
ST611FD-5	SS611FD-5	6	152	111/4	290	31/2	89	31/2	89
ST612FB-5	SS612FB-5	6	152	121/8	310	BLIND	13	31/2	89
ST614FD-5	SS614FD-5	6	152	14½	370	31/2	89	3½	89
ST616FD-5	SS616FD-5	6	152	161/4	410	31/2	89	31/2	89
ST618FB-5	SS618FB-5	6	152	18	460	BLIND	13	31//2	89
ST622FD-5	SS622FD-5	6	152	221/4	560	31/2	89	31/2	89
ST624FB-5	SS624FB-5	6	152	24	610	BLIND	13	31/2	89
ST624FE-5	SS624FE-5	6	152	24	610	BLIND	13	41//8	105
ST624FF-5	SS624FF-5	6	152	24	610	BLIND	13	41/2	114
ST629FD-5	SS629FD-5	6	152	28¾	730	31/2	89	31/2	89
ST630FB-5	SS630FB-5	6	152	30	760	BLIND	13	31/2	89
ST630FD-5	SS630FD-5	6	152	30	760	31/2	89	31/2	89
ST630FE-5	SS630FE-5	6	152	30	760	BLIND	13	41/8	105
ST630FF-5	SS630FF-5	6	152	30	760	BLIND	13	41/2	114
ST633FB-5	SS633FB-5	6	152	331/4	840	BLIND	13	31/2	89
ST633FD-5	SS633FD-5	6	152	331/4	840	31/2	89	31/2	89
ST636FB-5	SS636FB-5	6	152	36	910	BLIND	13	31/2	89
ST636FD-5	SS636FD-5	6	152	36	910	31/2	89	31/2	89
ST636FE-5	SS636FE-5	6	152	36	910	BLIND	13	41//8	105
ST636FF-5	SS636FF-5	6	152	36	910	BLIND	13	41/2	114
ST638FD-5	SS638FD-5	6	152	38	965	31/2	89	31/2	89
ST640FD-5	SS640FD-5	6	152	40	1020	31//2	89	31/2	89
ST640FE-5	SS640FE-5	6	152	40	1020	BLIND	13	41/8	105
ST640FF-5	SS640FF-5	6	152	40	1020	BLIND	13	41/2	114
ST643FB-5	SS643FB-5	6	152	43	1090	BLIND	13	3½	89
ST643FD-5	SS643FD-5	6	152	43	1090	31/2	89	31/2	89
ST644FB-5	SS644FB-5	6	152	44	1120	BLIND	13	31/2	89
ST644FD-5	SS644FD-5	6	152	44	1120	31/2	89	31/2	89
ST644FE-5	SS644FE-5	6	152	44	1120	BLIND	13	41/8	105
ST644FF-5	SS644FF-5	6	152	44	1120	BLIND	13	41/2	114
ST648FD-5	SS648FD-5	6	152	48	1220	31/2	89	3½	89
ST648FF-5	SS648FF-5	6	152	48	1220	BLIND	13	41/2	114
ST656FB-5	SS656FB-5	6	152	56	1420	BLIND	13	31/2	89
ST656FF-5	SS656FF-5	6	152	56	1420	BLIND	13	41/2	114

Due to our continuing program of improvement, specifications are subject to change without notice.