

SuperFlex™ Cartridges

M SERIES FILTER CARTRIDGES

See Section 1

VCS SERIES SUPERFLEX FILTER SEPARATOR CARTRIDGES

CC-23C Coalescer and CS-94 Separator Cartridge Data

- Provides two-stage coalescing and separation
- Recommended maximum operating temperature: 240°F
- Maximum differential pressure: 75 psi (5.25 kg/cm²)
- Flow direction: Outside to in
- pH range from 5 to 9
- All metal components coated to protect against corrosion

DIMENSIONS

MODEL NUMBER	MICRON RATING	OD		ID		NOMINAL LENGTH		NOMINAL LENGTH	
		in.	mm.	in.	mm.	in.	mm.	lbs.	kgs.
COALESCERS									
CC-23-7	1								
CC-23C	25	7 ⁵ / ₈	194	5 ⁵ / ₈	143	13 ¹¹ / ₁₆	350	4	1.8
SEPARATORS									
CS-94	5								
CS-94C	25	4 ¹ / ₈	105	1 ⁷ / ₈	48	10 ¹ / ₂	270	3	1.4

All dimensions and weights are approximate.

AGS SERIES SUPERFLEX AIR/GAS SEPARATOR CARTRIDGES

CC-23-7 Coalescer and CS-98 Separator Cartridge Data

- Provides two-stage separation and filtration
- Recommended maximum operating temperature: 240°F
- Maximum differential pressure: 75 psi (5.25 kg/cm²)
- Flow direction: Outside to in
- pH range from 5 to 9
- All metal components coated to protect against corrosion

DIMENSIONS

MODEL NUMBER	MICRON RATING	OD		ID		NOMINAL LENGTH		NOMINAL LENGTH	
		in.	mm.	in.	mm.	in.	mm.	lbs.	kgs.
COALESCERS									
CC-23-7	0.5	7 ⁵ / ₈	194	5 ⁵ / ₈	143	13 ¹¹ / ₁₆	350	4	1.8
SEPARATORS									
CS-98-2	3	4 ¹ / ₈	105	1 ⁷ / ₈	48	10 ¹ / ₂	270	3	1.4

All dimensions and weights are approximate.

Due to our continuing program of improvement, specifications are subject to change without notice.